


## Boundary Element Method Open Source Software in Excel VBA

File / Module(s)	<a href="#">LBEMA 1.xlsm</a> / LBEMA.xlsm
Title	A spreadsheet that solves Laplace's equation in an axisymmetric three-dimensional interior or exterior domain.
Version(Date) and History	<b>Version 1</b> (July 2017). This replaces LIBEMA (June 2017), which only worked on interior problems.
Description	<p>This Excel spreadsheet solves the three-dimensional axisymmetric Laplace equation<sup>1</sup> interior or exterior to a closed surface.</p> $\nabla^2 \varphi(\mathbf{p}) = 0 \quad . \quad (1)$ <p>by the boundary element method (BEM)<sup>2</sup>. This software can form the basis for solving a range of physical or engineering problems that can be resolved to the axisymmetric Laplace equation, such as steady state heat conduction, ideal fluid, steady state electrical potential and groundwater flow. The solution by the BEM is based on the direct and indirect integral equation reformulation<sup>3</sup> of the Laplace equation. The integral equations that arise are solved by collocation<sup>4</sup>. As part of the process of describing and approximating the boundary, it is represented by a set of conical panels<sup>5</sup>. The data is input and output via the sheets, this in particular utilises the main feature of the spreadsheet in order to allow us to visualise the data that we are setting and creating as we proceed with the stages of the method.</p> <div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;">  </div> <div style="text-align: center;"> <p>The diagram to the left illustrates a truncated conical panel. These can be used to build an axisymmetric surface with the nodes lying on the generator. This normally results in an approximation of an axisymmetric boundary S, and its approximation and the interior domain D. The initial Laplace problem is an interior problem and this is set up on the sheet <i>Set Interior Problem</i>. In order to set up the problem, the boundary must be defined, and this is carried out by approximating the boundary by a set of <math>n</math> conical panels<sup>5</sup>. The file LBEMA.xlsm sets up the test of a cylinder, as illustrated in the diagram on the right, with <math>\varphi</math> defined on the upper and lower surfaces and with <math>\frac{\partial \varphi}{\partial n} = 0</math> on the curved boundary. For example this could model a steady state heat conduction problem with a temperature of 10°C on the lower surface and 20°C on the upper surface and insulated on the curved surface.</p> </div> <div style="text-align: center;">  </div> </div>

Perhaps the unique selling point in the boundary element method is that only the boundary requires a mesh; most methods – such as the finite difference method and finite element method are *domain methods* that require a mesh through the domain.

Generally, on the spreadsheet, the areas coloured yellow are to be completed by the user, the blue areas are not to be altered and the computed solutions generally has a green background. Intermediate computations are left with a white background.

Nodes			Panels		
Number of nodes 25			Number of panels 24		
Index	r	z	index	node 1	node 2
1	0	1	1	1	2
2	0.125	1	2	2	3
3	0.25	1	3	3	4
4	0.375	1	4	4	5
5	0.5	1	5	5	6
6	0.625	1	6	6	7
7	0.75	1	7	7	8
8	0.875	1	8	8	9
9	1	1	9	9	10
10	1	0.875	10	10	11
11	1	0.75	11	11	12

The definition of the boundary


INTERIOR?  
TRUE

Since it is an interior problem this is flagged on the sheet by setting it as 'TRUE@'. The boundary is defined by 25 points or nodes lying on the boundary generator or and  $n_S=24$  and the panels are defined by linking these points. The first two sets of columns for the cylinder test problem are shown on the left. The generator nodes with coordinates  $(r,z) = (0,1), (0.125,1), (0.25,1)...$  are stated in the set of columns with the title Nodes. This also indexes the points as they progress around the boundary. The number of nodes is stated at the top (in this example there are 25). In the second set of columns termed Panels, which lists the index of each panel in the first column. The number of panels  $n_S$  is stated (in this example  $n_S=24$ ). The next two columns state the indices (as defined in the Nodes columns) that are at either end of the generator of each panel. For example the first panel (index 1) links vertex 1  $(r,z) = (0,1)$  to vertex 2  $(0.125,1)$ .

The boundary condition is defined on the table on the right.

Boundary Condition			
Number of panels			24
index	alpha	beta	f
1	1	0	20
2	1	0	20
3	1	0	20
4	1	0	20
5	1	0	20
6	1	0	20
7	1	0	20
8	1	0	20
9	0	1	0
10	0	1	0
11	0	1	0

The boundary condition on each panel of the cylinder



The solution is normally required in the domain, or, more precisely, at a set of domain points. These points must be listed on the *Set Interior Problem* sheet in the table *Interior Points*. The number of interior points  $n_D$  (=5) is stated at the top of the table. The coordinates of the chosen points are listed in the table on the right specifying the (r,z) coordinates of the interior points where the solution is sought. When processing, the spreadsheet generates a sketch of the generator of the boundary and the interior points to the left on the sheet *Sketch*. For an interior problem, the nodes on a panel on the outer boundary must be ordered clockwise around the boundary. If there are inner surfaces then each panel's vertices must be arranged in the anticlockwise order around the boundary.

Interior Points		
Number of points		5
index	x	y
1	0.25	0.25
2	0.75	0.25
3	0.25	0.75
4	0.75	0.75
5	0.5	0.5

The functions defined on the boundary are represented at the mid-points of each panel; the collocation points  $\mathbf{p}_i$  for  $i = 1..n$ . A boundary condition must be set and this is defined in the most general Robin form at every collocation point  $\mathbf{p}_i$ ,

$$\alpha(\mathbf{p}_i)\varphi(\mathbf{p}_i) + \beta(\mathbf{p}_i)\frac{\partial\varphi}{\partial n_p}(\mathbf{p}_i) = f(\mathbf{p}_i) \quad (\mathbf{p}_i \in S) \quad (2)$$

the boundary and boundary condition together forming the boundary value problem<sup>6</sup>. For simplicity, the notation  $\varphi_{S_i} = \varphi(\mathbf{p}_i)$ ,  $v_{S_i} = \frac{\partial\varphi}{\partial n_p}(\mathbf{p}_i)$ ,  $\alpha_{S_i} = \alpha(\mathbf{p}_i)$ ,  $\beta_{S_i} = \beta(\mathbf{p}_i)$  and  $f_{S_i} = f(\mathbf{p}_i)$ . The boundary condition is set on the spreadsheet in the *Boundary Condition* column. The number of panels and the panel indices are already set (so they are in blue).

The solution is that of a simple gradient between  $\varphi = 10$  on the lower surface of the cylinder and  $\varphi = 20$  on the upper surface. For simplicity, let us write  $\mathbf{p}=(r,z)$ , and formally the solution is

$$\varphi(\mathbf{p}) = 10 + 10z \quad (3)$$

which is clearly a solution of Laplace's equation (1), that also fits the boundary condition.

The boundary conditions and the solutions on the boundary are principally located at the centres of the panels. By pressing the button on the right, a preliminary check is carried out on the boundary. The panels that make up the separate boundaries are placed on the *Closed Boundaries* sheet, a sketch of the boundary is placed on the sheet *Sketch*, as shown above on the left, and the  $(r,z)$  coordinates of the centres of the panels are listed as shown on the right.

Once the mesh and boundary conditions are defined, the boundary element method computation follows several stages, which are decoupled in the spreadsheet. The spreadsheet provides a practical and versatile boundary element method for solving axisymmetric interior three-dimensional Laplace or *potential* problems, but the aim is also to use the spreadsheet to illustrate the method in action, with interim results at each stage. The visible results in LBEMA.xlsm file also provides a supporting document for development of the axisymmetric BEM in this and other programming languages.

A boundary element method is based on an integral equation reformulation of the partial differential equation. There are two fundamentally distinct approaches to deriving the integral equation, one is historically termed the *direct method* and the other one termed the *indirect method* and both of these methods will be applied within the spreadsheet. The two methods both require the discretisation of the integral operators defined on the boundary, replacing the boundary integral operators by matrices<sup>9</sup>.

Panel Centres		
Number of panels		24
index	r-centre	z-centre
1	0.0625	1
2	0.1875	1
3	0.3125	1
4	0.4375	1
5	0.5625	1
6	0.6875	1
7	0.8125	1
8	0.9375	1
9	1	0.9375
10	1	0.8125

The coordinates of the centers of the generator of the panels

The matrices that are required by the two methods for determining the solution on the boundary are termed  $L_{SS}$ ,  $M_{SS}$  and  $M_{SS}^t$ , all are  $n_S \times n_S$  matrices. Once a solution on the boundary is obtained the  $L_{DS}$ ,  $M_{DS}$  matrices are required to find the solution in the domain and these are all  $n_D \times n_S$  matrices. The matrices are generated once the button to the right on the sheet *Set Interior Problem* is pressed. The matrices are each listed explicitly on separate sheets.

Form BEM Matrices  
L\_SS,M\_SS,Mt\_SS,L\_DS,M\_DS

For this test problem, the sheets L\_SS, M\_SS and M\_t\_SS list the contents of the 24×24 matrices and L\_DS and M\_DS list the contents of the 5×24 matrices.

On pressing the button on the left the direct solution is generated and placed on the sheet *Direct Solution*. The approximations to  $\varphi$  and  $\frac{\partial \varphi}{\partial n}$  on the boundary is found by solving the linear system of equations

Direct Solution

$$(M_{SS} + \frac{1}{2}I)\hat{\varphi}_S = L_{SS}\hat{v}_S \quad (3)$$

alongside the equations representing the boundary condition (2).

The solution at the domain points is then found using the following matrix multiplications

$$\hat{\varphi}_D = L_{DS}\hat{v}_S - M_{DS}\hat{\varphi}_S \quad (4)$$

On pressing the button on the right the indirect solution is generated and placed on the sheet *Indirect Solution*. In the indirect method a layer potential  $\sigma_{0_S}$  is introduced, a function defined on the surface, but having no physical meaning.

Indirect Solution

Its value can be obtained through solving the following system of equations

$$(D_\alpha L_{SS} + D_\beta (M_{SS}^t + \frac{1}{2}I)) \widehat{\sigma}_{0_S} = \underline{f}_S. \quad (5)$$

where  $D_\alpha$  and  $D_\beta$  are diagonal matrices with  $[D_\alpha]_{ii} = \alpha_{Si}$  and  $[D_\beta]_{ii} = \beta_{Si}$ . Once  $\widehat{\sigma}_{0_S}$  is found the solution on the boundary and the solution at the domain points can be found using the matrix-vector multiplications

$$\underline{\hat{\phi}}_S = L_{SS} \widehat{\sigma}_{0_S}, \quad \underline{\hat{v}}_S = (M_{SS}^t + \frac{1}{2}I) \widehat{\sigma}_{0_S}, \quad \underline{\hat{\phi}}_D = L_{DS} \widehat{\sigma}_{0_S}. \quad (6)$$

The results from the test problem are placed on the sheets *Direct Solution* and *Indirect Solution*. The solution at the collocation points on the boundary is given and the solution at the domain points. The latter results for the two methods applied to the test problem are given below and these may be compared with the exact solution (3).

Solution at the interior points by the direct BEM			Solution at the interior points by the indirect BEM		
Solution in D			Solution in D		
Number of points		5	Number of points		5
index	phi_D		index	phi_D	
1	12.49899		1	12.97962	
2	12.49437		2	12.4966675	
3	17.50116		3	17.4993183	
4	17.50603		4	17.489655	
5	15.00016		5	14.9959348	

Although the solution for the 24 element boundary element method seem fast on the spreadsheet, it is important in general to have an overview of computational costs within the boundary element method, especially for the cases in which a much larger number of elements are required. Clearly the formation of the  $*_{SS}$  matrices is  $O(n_S^2)$  and the  $*_{DS}$  matrices is  $O(n_D n_S)$ , using O notation<sup>10</sup>. The solution of the linear systems are carried out by the most obvious method of LU factorisation and back substitution<sup>11</sup>, using the VBA functions LUFac and LUFbSub, although the direct BEM also requires the wrapper of the *gls* method<sup>11</sup> that carries out swapping of the columns of the matrices in preparation for LU factorisation. The solution of the matrices by this sort of method is generally characterised as  $O(n_S^3)$ . The matrix multiplications involved are  $O(n_S^2)$  or  $O(n_D n_S)$ , and they are of lower order and so they can usually be subsumed into the  $O(n_S^3)$ .

Although the computational cost of the matrix-vector solutions is apparently an order greater than the cost of forming the matrices, the matrix elements usually require a numerical integration<sup>13</sup> to obtain their value and hence the computational cost of the matrix solution will normally exceed the computational cost of the determination of the matrices for higher values of  $n_s$ .


Once the matrices have been found and factorised, the computational cost of the back substitution is  $O(n_s^2)$ . Hence it makes sense to save the factorised matrix and the other necessary information that is required to find a new solution. At this stage the boundary and for of the boundary condition are set. However the  $f$ -values can be changed and new solutions found from the saved values.

The sheet *Set Interior Problem* is for setting up the boundary and boundary condition for the initial problem to be solved. The points in the domain at which the solution is sought is also stated. Pressing the button Form BEM Matrices generates the matrices required to implement the method and lists the contents of the matrices on the appropriate sheet.

If the direct method is used then two matrices are saved on the sheets *A\_gls* and *B\_gls* and further information on the sheet *perm xory*, that result from *gl*s method and the embedded LU factorisation. If the indirect method is used then the LU factorisation of the matrix and further information are stored on the sheets *Indirect\_LU* and *perm*. If another run of the method (with the same boundary definition and the same  $\alpha$ - and  $\beta$ -values) then this (the  $f$ -values) can be placed on the sheet *New Interior Condition*. On that sheet, the buttons *New direct solution* and *New indirect solution*, completes the new solutions and places them in the sheets *New Direct Solution* and *New Indirect Solution*.

In order to test the method for finding the secondary solutions, the boundary condition was changed so that  $\varphi=20$  on the lower surface of the square and  $\varphi=10$  on the upper surface. The altered boundary condition is placed on the sheet *New Int Problem Condition*. The solutions on the *New Direct Solution* and *New Indirect Solution* sheets are given below, and these mirror the previous results, as expected.

Solution at the interior points by the direct BEM			Solution at the interior points by the indirect BEM		
Solution in D			Solution in D		
Number of points	5		Number of points	5	
index	phi_D		index	phi_D	
1	17.50116488		1	17.49931832	
2	17.50603426		2	17.48986549	
3	12.49898847		3	12.49796196	
4	12.49437017		4	12.49666754	
5	15.00015902		5	14.9959348	



The spreadsheet has the facility to solve exterior problems and this follows a similar routine as for the interior problems described earlier. In order to run an exterior problem on the spreadsheet the spreadsheet sheet *Set Exterior Problem* needs to be completed. The 'INTERIOR' flag must be set as 'FALSE'. The test problem is that of a sphere of radius 1.0 described by 20 panels indexed from the top to the bottom. The solution points are  $(r,z) = (0,2), (0,-2), (1,1), (1,-1)$  and  $(2,0)$ . When it is processed, an illustration of the generator and solution points is given on the sheet *Sketch*.

INTERIOR?  
FALSE

The analytic solution that will be applied is

$$\varphi = \frac{1}{r}$$

A Dirichlet boundary condition is applied on the upper surface of the sphere and a Neumann boundary condition is applied on the lower surface. Hence  $\varphi=1$  is the boundary condition on the upper hemisphere. In order to determine the Neumann boundary condition we note that

$$\frac{\partial \varphi}{\partial n} = \frac{\partial \varphi}{\partial r} \frac{\partial r}{\partial n} = \frac{-1}{r^2} \cdot 1 = -\frac{1}{r^2},$$

and hence  $\frac{\partial \varphi}{\partial n} = -1$  is the boundary condition on the lower hemisphere. The matrices are formed and the direct and indirect solutions are obtained in the same way as described earlier.

If you want to run the solution again but with just a change in  $f$  then this may be carried out on the *New Ext Problem Condition* sheet. On this sheet the problem is re-run with the analytic solution  $\varphi = \frac{2}{r}$ . Hence the boundary condition values are doubled.

Web source of code.	<a href="http://www.boundary-element-method.com/Excel_VBA/LBEMA_1.xlsm">www.boundary-element-method.com/Excel_VBA/LBEMA_1.xlsm</a>
Web source of this guide	<a href="http://www.boundary-element-method.com/Excel_VBA/LBEMA_xls_1.pdf">www.boundary-element-method.com/Excel_VBA/LBEMA_xls_1.pdf</a>
Web source of the algorithm	<a href="http://www.boundary-element-method.com/laplace">http://www.boundary-element-method.com/laplace</a>
Dependent routines	<p><u>Internal Routines</u>  Module for computing the boundary element matrices <math>L_{SS}</math>, <math>M_{SS}</math>, <math>M_{SS}^f</math>, <math>L_{DS}</math>, and <math>M_{DS}</math>: <a href="#">lbemaMat.bas</a>  Module for solving the interior Laplace problem by the direct BEM: <a href="#">lbemaSolveDirect.bas</a>  Module for computing additional solutions from the direct BEM: <a href="#">reSolveDirect.bas</a>  Module for solving the interior Laplace problem by the indirect BEM: <a href="#">lbemsSolveIndirect.bas</a>  Module for computing additional solutions from the direct BEM: <a href="#">reSolveDirect.bas</a>  Module for verifying the geometry of the boundary and solution points: <a href="#">VBNDRY.bas and Verify ComonBoundaryData.bas</a></p> <p><u>External Routines</u>  Module for computing each element of the matrices: <a href="#">l3alc.bas</a> from <a href="#">l3alc.xlsm</a>  gls algorithm, carrying out column swaps in the matrices in order to prepare for LU factoriation: <a href="#">gls.bas</a> from <a href="#">GLS.xlsm</a>  regls algorithm, carrying out additional solutions , following the application of gls : <a href="#">regls.bas</a> from <a href="#">GLS.xlsm</a>  Module for carrying out LU factorisation: <a href="#">LUfac.bas</a> from <a href="#">LUfac.xlsm</a>  Module for carrying out the forward and back substitution to find the solution following Lufbsub from <a href="#">LUfac.xlsm</a>  Utility routines for 2D geometry: <a href="#">GEOM2D.bas</a> module from <a href="#">GEOM.xlsm</a>  Utility module for setting the quadrature rule; <a href="#">gl*</a>  Verification module for checking the input geometry; <a href="#">VG3alc</a> (that calls <a href="#">VG2lc.bas</a>)  Verification module for checking the input quadrature rule; <a href="#">VQuad.bas</a> in <a href="#">VQuad.xlsm</a></p>
Test problems or modules tested	Testing <a href="#">lbem2mat.bas</a> , <a href="#">LBEMASolveDirec</a> , <a href="#">LBEMASolveIndirect.bas</a> , <a href="#">reSolveDirect.bas</a> , <a href="#">reSolveIndirect.bas</a> contained in this file.
Licence	This is 'open source'; the software may be used and applied within other systems as long as its provenance is appropriately acknowledged. See the <a href="#">GNU Licence</a> for more information or contact <a href="mailto:webmaster@boundary-element-method.com">webmaster@boundary-element-method.com</a> .
Codes that this may be used alongside this	Not applicable.

Commented [SK1]:

one	
Similar codes that may be of interest	The initial concept of the core code are based on the Acoustics, Laplace and Helmholtz libraries in Fortran. ( <a href="http://www.boundary-element-method.com">www.boundary-element-method.com</a> ). This also builds on the concepts in the <a href="#">Matlab/Freemat/Octave Scilab Laplace library</a> .
Applications	Potential problems: eg steady state heat conduction, steady state electric fields.
Author	<a href="#">Stephen Kirkup</a>
References	<ol style="list-style-type: none"><li>1. <a href="#">Laplace's Equation</a></li><li>2. <a href="http://www.boundary-element-method.com">www.boundary-element-method.com</a></li><li>3. <a href="#">Integral Equation Formulation of the Interior Laplace Problem</a></li><li>4. <a href="#">Solution of Fredholm Integral Equations by Collocation</a></li><li>5. <a href="#">Representation of a line by flat panels</a></li><li>6. <a href="#">Boundary Value Problems and Boundary Conditions</a></li><li>7. <a href="#">Finite Difference Method</a></li><li>8. <a href="#">Finite Element Method</a></li><li>9. <a href="#">Boundary Element Method for the Interior Laplace Problem</a></li><li>10. <a href="#">Big O Notation in Computing</a></li><li>11. <a href="#">LU Factorisation and the solution of linear systems of equations</a></li><li>12. <a href="http://www.boundary-element-method.com/gls.htm">http://www.boundary-element-method.com/gls.htm</a></li><li>13. <a href="#">Numerical Integration</a></li></ol>